



NOTE.

- The shape and appearance of assembly differ a little with nominal size compared to this drawing.

DIMENSIONS TABLE

Nominal Size		d	ANSI Class 150			L	D	W	D ₂	D ₃	H	H ₁	A ₁	A ₂	A ₃	A ₄	ACTUATOR TYPE
			C	n	h												
2"	50mm	2.17	4.75	2 (4)	0.75	1.73	3.54	4.57	3.54	6.30	12.52	2.40					
3	80	3.15	6.00	— (4)	0.75	2.13	4.92	5.98	3.54	6.30	13.27	3.74	6.57	7.32	4.09	11.26	SRJ-010
4	100	3.94	7.50	4 (8)	0.75	2.32	6.06	6.85	3.54	6.30	13.90	3.90					
5	125	4.92	8.50	4 (8)	0.88	2.52	7.13	8.11	5.51	6.30	15.59	4.72	6.57	7.32	4.09	11.26	SRJ-020
6	150	5.91	9.50	4 (8)	0.88	2.95	8.31	9.29	5.51	6.30	16.26	5.39					
8	200	7.52	11.75	4 (8)	0.88	3.35	10.43	11.10	4.92	9.65	17.32	6.42	7.52	7.95	5.12	12.99	SRJ-060
10	250	9.65	14.25	4 (12)	1.00	3.78	12.80	13.43	4.92	9.65	18.70	7.87					

Unit : inch

27	KEY (A)	1	CORON STEEL (S45C)	
26	STEM BUSH	1	CORON STEEL (S45C)	
24	BOLT (E)	4	STAINLESS STEEL (SUS304)	
23	BOLT (D)	4	STAINLESS STEEL (SUS304)	Used for Size 5", 6"
21	STAND	1	STEEL (SS400)	Used for Size 5", 6" Epoxy Coat.
20	ACTUATOR	1	ALUMINUM ALLOY etc.	Epoxy Coat.
1	BUTTERFLY VALVE (TYPE 55)	0-RING	EPDM	Epoxy Powder Coat.
		SEAT	PTFE	
		DISC	PTFE	
		BODY	DUCTILE CAST IRON (FCD450)	
No.	DESCRIPTION	QTY.	MATERIAL	REMARKS

ITEM	BUTTERFLY VALVE (TYPE 55)S) ELECTRIC ACTUATED S TYPE ASS'Y ANSI Class 150 2" (50mm) ~ 10" (250mm)			
DRAWN	M.Iwakiri	DATE	SCALE	
CHECKED	H.Kawano	SEP.5.2019	~	
APPROVED	K.Koushou	DRAWING No.		
		55-AE003AE		△
SPECIAL ORDER No.	ASAHI YUKIZAI CORPORATION			