



NOTE.

- The shape and appearance of assembly differ a little with nominal size compared to this drawing.

DIMENSIONS TABLE

Unit : mm

Nominal Size	d	ANSI Class 150			L	D	W	D ₂	D ₃	H	H ₁	A ₁	A ₂	A ₃	A ₄	ACTUATOR TYPE	
		C	n	h													
50mm 2"	55	120.5	2 (4)	19	44	90	116	90	160	318	61						
80 3	80	152.5	— (4)	19	54	125	152	90	160	337	95	167	186	104	286	SRJ-010	
100 4	100	190.5	4 (8)	19	59	154	174	90	160	353	99						
125 5	125	216.0	4 (8)	22	64	181	206	140	160	396	120	167	186	104	286	SRJ-020	
150 6	150	241.5	4 (8)	22	75	211	236	140	160	413	137						
200 8	191	298.5	4 (8)	22	85	265	290	125	245	440	163	191	202	130	330	SRJ-060	
250 10	245	362.0	4 (12)	25	96	325	341	125	245	475	200						

27	KEY (A)	1	CORBON STEEL (S45C)	
26	STEM BUSH	1	CORBON STEEL (S45C)	
24	BOLT (E)	4	STAINLESS STEEL (SUS304)	
23	BOLT (D)	4	STAINLESS STEEL (SUS304)	Used for Size 125, 150mm
21	STAND	1	STEEL (SS400)	Used for Size 125, 150mm Epoxy Coat.
20	ACTUATOR	1	ALUMINUM ALLOY etc.	Epoxy Coat.
1	BUTTERFLY VALVE (TYPE 55)	O-RING	EPDM	Epoxy Powder Coat.
		SEAT	PTFE	
		DISC	PTFE	
		BODY	DUCTILE CAST IRON (FCD450)	
No.	DESCRIPTION	QTY.	MATERIAL	REMARKS

ITEM	BUTTERFLY VALVE (TYPE 55)S) ELECTRIC ACTUATED S TYPE ASS'Y ANSI Class 150 50mm (2") ~250mm (10")			
DRAWN	M.Iwakiri	DATE	SCALE	
CHECKED	H.Kawano	SEP.5.2019	DRAWING No.	
APPROVED	K.Koushou	55-AE003AEm	△	
SPECIAL ORDER No.	ASAHI YUKIZAI CORPORATION			