



DIMENSIONS TABLE

Nominal Size	d	DIN PN10			L	D	W	D ₂	D ₃	H	H ₁	A ₁	A ₂	A ₃	A ₄	ACTUATOR TYPE	
		C	n	h													
50mm 2"	55	125	2 (4)	18	44	90	116	90	160	318	61						
80 3	80	160	4 (8)	18	54	125	152	90	160	337	95	167	186	104	286	SRJ-010	
100 4	100	180	4 (8)	18	59	154	174	90	160	353	99						
125 5	125	210	4 (8)	18	64	181	206	140	160	396	120						
150 6	150	240	4 (8)	22	75	211	236	140	160	413	137	167	186	104	286	SRJ-020	
200 8	191	295	4 (8)	22	85	265	282	125	245	440	163	191	202	130	330	SRJ-060	
250 10	245	350	4 (12)	22	96	325	341	125	245	475	200						

Unit : mm

NOTE.

- The shape and appearance of assembly differ a little with nominal size compared to this drawing.

No.	DESCRIPTION	QTY.	MATERIAL	REMARKS
27	KEY (A)	1	CORON STEEL (S45C)	
26	STEM BUSH	1	CORON STEEL (S45C)	
24	BOLT (E)	4	STAINLESS STEEL (SUS304)	
23	BOLT (D)	4	STAINLESS STEEL (SUS304)	Used for Size 125, 150mm
21	STAND	1	STEEL (SS400)	Used for Size 125, 150mm Epoxy Coat.
20	ACTUATOR	1	ALUMINUM ALLOY etc.	Epoxy Coat.
1	BUTTERFLY VALVE (TYPE 55)	Ø-RING	EPDM	Epoxy Powder Coat.
		SEAT	PTFE	
		DISC	PTFE	
		BODY	DUCTILE CAST IRON (FCD450)	

ITEM	BUTTERFLY VALVE (TYPE 55) ELECTRIC MODEL S TYPE ASS'Y DIN PN10 50mm (2") ~250mm (10")			
DRAWN	M.Iwakiri	DATE	SCALE	
CHECKED	H.Kawano	SEP.5.2019		
APPROVED	K.Koushou	DRAWING No.		
		55-AE003DE		△
SPECIAL ORDER No.	ASAHI YUKIZAI CORPORATION			