



Note. Operating pressure 0.4~0.7 MPa G
 Air to open : Air-less shut
 Air to shut : Air-less open

157	SCREW (F)	4	STAINLESS STEEL (SUS304)	
1a	RING	2	STEEL (SS400) with Epoxy Powder Coat.	
39	BOLT·NUT (P)	4sets	STAINLESS STEEL (SUS304)	
38	BOLT (E)	4	STAINLESS STEEL (SUS304)	
37a	SCREW (C)	1	STAINLESS STEEL (SUS304)	
37	JOINT (A)	1	COPPER ALLOY (C3604)	
35	ACTUATOR	1	CAST IRON (FC200) etc.	Acryl Coat.
30	STAND	1	CAST ALUMINIUM ALLOY (AC4C)	Epoxy Coat.
8	STEM HOLDER (A)	1	PP	
7	STEM	1	STAINLESS STEEL (SUS403)	
6	O-RING (C)	1		
5	O-RING (B)	2	<input type="checkbox"/> EPDM <input type="checkbox"/> FKM	
4	O-RING (A)	2	<input type="checkbox"/> Others ()	
3	SEAT	1		
2	DISC	1	BODY/DISC <input type="checkbox"/> PP/PP <input type="checkbox"/> PVDF/PVDF	
1	BODY	1		
No.	DESCRIPTION	QTY.	MATERIAL	REMARKS

DIMENSIONS TABLE

Unit : inch

Nominal Size	d	ANSI Class 150				L	D	D ₁	D ₂	H	H ₁	A	A ₁	A ₂	A ₃	P	Actuator Type
		C	n	h													
16"	400mm	15.98	21.25	16	1.12	6.65	23.62	18.50	9.25	29.80	11.81	37.13	13.07	7.17	4.65	3/8	TA-200R

ITEM	BUTTERFLY VALVE (TYPE56) PNEUMATIC MODEL TA TYPE ASS'Y <input type="checkbox"/> AIR TO OPEN, <input type="checkbox"/> AIR TO SHUT ANSI Class 150 : 16" (400mm)		
DRAWN	E.Ozaki	DATE	SCALE
CHECKED	H.Kawano	JAN.22.2018	
APPROVED	H.Kourogi	DRAWING No. 56-AA003AE	
SPECIAL ORDER No.	ASAHI YUKIZAI CORPORATION		