



Note. Operating pressure 0.4~0.7 MPa G
 Air to open : Air-less shut
 Air to shut : Air-less open

157	SCREW (F)	4	STAINLESS STEEL (SUS304)	
1a	RING	2	STEEL (SS400) with Epoxy Powder Coat.	
39	BOLT·NUT (P)	4sets	STAINLESS STEEL (SUS304)	
38	BOLT (E)	4	STAINLESS STEEL (SUS304)	
37a	SCREW (C)	1	STAINLESS STEEL (SUS304)	
37	JOINT (A)	1	COPPER ALLOY (C3604)	
35	ACTUATOR	1	CAST IRON (FC200) etc.	Acryl Coat.
30	STAND	1	CAST ALUMINIUM ALLOY (AC4C)	Epoxy Coat.
8	STEM HOLDER (A)	1	PP	
7	STEM	1	STAINLESS STEEL (SUS403)	
6	O-RING (C)	1		
5	O-RING (B)	2	□EPDM □FKM	
4	O-RING (A)	2	□Others ()	
3	SEAT	1		
2	DISC	1	BODY/DISC □PP/PP	
1	BODY	1	□PVDF/PVDF	
No.	DESCRIPTION	QTY.	MATERIAL	REMARKS

DIMENSIONS TABLE

UNIT : mm

Nominal Size	d	ANSI Class 150			L	D	D ₁	D ₂	H	H ₁	A	A ₁	A ₂	A ₃	P	Actuator Type
		C	n	h												
400mm 16"	406	539.5	16	29	169	600	470	235	757	300	943	332	182	118	3/8	TA-200R

ITEM	BUTTERFLY VALVE (TYPE56) PNEUMATIC MODEL TA TYPE ASS'Y <input type="checkbox"/> AIR TO OPEN, <input type="checkbox"/> AIR TO SHUT ANSI Class 150 : 400 ^{mm} (16 ["])		
DRAWN	E.Emmei	DATE	SCALE
CHECKED	H.Kawano	JUL.16.2019	~
APPROVED	K.Koushou	DRAWING No. 56-AA003AEm	
SPECIAL ORDER No.	ASAHI YUKIZAI CORPORATION		