



DIMENSIONS TABLE

Nominal Size	d	JIS 5K			JIS 10K			L	D	D1	D2	D3	H	H1	A1	A2	A3	A4	Actuator Type
		C	n	h	C	n	h												
40mm 1½"	45	95	4	15	105	4	19	39	150	71	100	160	313	75	167	186	104	286	SRJ-010
50 2	56	105	4	15	120	4	19	42	165	81	100	160	323	83					
65 2½	69	130	4	15	140	4	19	46	185	95	100	160	333	93					
80 3	77	145	4	19	150	8	19	46	211	105	100	160	348	106					
100 4	102	165	8	19	175	8	19	56	238	134	100	160	363	119	167	186	104	286	SRJ-020
125 5	129	200	8	19	210	8	23	66	255	169	140	160	398	128					
150 6	150	230	8	19	240	8	23	71	285	190	140	160	413	143					
200 8	195	280	8	23	290	12	23	87	350	242	140	245	441	175	191	202	130	330	SRJ-060
250 10	250	345	12	23	355	12	25	112	421	302	180	245	476	211					

Unit : mm

NOTE. The shape and appearance of assembly differ a little with nominal size compared to this drawing.

157	SCREW (F)	4	STAINLESS STEEL (SUS304)	
40	KEY (B)	1	CARBON STEEL (S45C)	
39	BOLT (K)	4	STAINLESS STEEL (SUS304)	
38	BOLT (E)	4	STAINLESS STEEL (SUS304)	Used for Size 125, 150mm
36	STEM BUSH	1	CARBON STEEL (S45C)	
35	ACTUATOR	1	ALUMINUM ALLOY etc.	Epoxy Coat.
30	STAND	1	CHROMIZED STEEL (SS400)	Used for Size 125, 150mm Epoxy Coat.
8	STEM HOLDER (A)	1	PP	
7	STEM	1	□ STAINLESS STEEL (SUS403) □ STAINLESS STEEL (SUS316)	
185	O-RING (I)	4	□ EPDM	
6	O-RING (C)	1	□ FKM	
3	SEAT	1	()	
184	SEAT BUSH (B)	1	BODY/ DISC- SEAT BUSH	
183	SEAT BUSH (A)	1	□ PVC/PP	
2	DISC	1	□ PP/PP	
1	BODY	1	□ PVDF/PVDF	
No.	DESCRIPTION	QTY.	MATERIAL	REMARKS

ITEM	BUTTERFLY VALVE (TYPE 57) ELECTRIC ACTUATED S TYPE ASS'Y □ JIS 5K, □ JIS 10K : 40mm (1½") ~ 250mm (10")		
DRAWN	K.Sakiyama	DATE	SCALE
CHECKED	H.Kawano	JAN.26.2018	~
APPROVED	H.Kouroggi	DRAWING No.	
SPECIAL ORDER No.	57-AE007JE		4
ASAHI YUKIZAI CORPORATION			