



204	GASKET (O)	1	EPDM	
157	SCREW (F)	4	STAINLESS STEEL (SUS304)	
1a	RING	2	STEEL (SS400) with Epoxy Powder Coat.	
39	BOLT (K)	4	STAINLESS STEEL (SUS304)	
36	STEM BUSH	1	CARBON STEEL (S45C)	
35	ACTUATOR	1	DUCTILE IRON (FCD450) etc.	Epoxy coat.
8	STEM HOLDER (A)	1	PP	
7b	SNAPRING	1	STAINLESS STEEL (SUS304)	
7a	KEY (A)	1	CORBON STEEL (S45C)	
7	STEM	1	STAINLESS STEEL (SUS403)	
6	O-RING (C)	1		
5	O-RING (B)	2	<input type="checkbox"/> EPDM <input type="checkbox"/> FKM <input type="checkbox"/> Others	
4	O-RING (A)	2		
3	SEAT	1		
2	DISC	1	<input type="checkbox"/> BODY/DISC <input type="checkbox"/> PP/PP <input type="checkbox"/> PVDF/PVDF	
1	BODY	1		
No.	DESCRIPTION	QTY.	MATERIAL	REMARKS

DIMENSIONS TABLE

UNIT : mm

NOMINAL SIZE	DIN PN10				D		D <sub>1</sub>	D <sub>2</sub>	L	H	H <sub>1</sub>	H <sub>2</sub>	I	Actuator Type	Motor Rating Output (Kw)
	d	C	n	h	PP	PVDF									
450mm 18"	452	565	20	26	633	630	525	340	179	468	315	373	752	LTRM-01/BRM-2 or LTRH-01/BRM-2 (AUTO-RECOVERY TYPE) (MANUAL RECOVERY TYPE)	0.4
500	502	620	20	26	683	680	575	340	190	498	350	403	782		
600	603	725	20	30	793	790	686	340	209	563	424	468	847		

NOTE. The shape and appearance of assembly differ a little with nominal size compared to this drawing.

ITEM	BUTTERFLY VALVE (TYPE75) ELECTRIC ACTUATED S TYPE ASS'Y □AUTO-RECOVERY TYPE, □MANUAL RECOVERY TYPE DIN PN10 450mm (18") ~600mm (24")		
DRAWN	E.Ozaki	DATE	SCALE
CHECKED	H.Kawano	JAN.30.2018	
APPROVED	H.Kourogi	DRAWING No. BF-AE004DE	
SPECIAL ORDER No.	ASAHI YUKIZAI CORPORATION		