



131	STEM HOLDER (C)	1	PP	
24	CAP (A)	1	PP	
23	SCREW (B)	4	STAINLESS STEEL (SUS304)	
22	LOCKING PLATE	1	PPG	
21	BOLT (B)	1	STAINLESS STEEL (SUS304)	
20	WASHER (A)	1	STAINLESS STEEL (SUS304)	
19	SPRING	1	STAINLESS STEEL (SUS304)	
18	PIN	1	PPG	
17	HANDLE LEVER	1	PPG	
16a	INSERTED METAL OF HANDLE	1	STAINLESS STEEL (SUS316)	
16	HANDLE (A)	1	PP	
9	BOLT (A)	3	STAINLESS STEEL (SUS304)	
6	O-RING (C)	1	<input type="checkbox"/> EPDM <input type="checkbox"/> FKM <input type="checkbox"/> others ( )	
7	STEM	1	PP	
2	DISC	1	PP	
1	BODY	1	PP	
No.	DESCRIPTION	QTY.	MATERIAL	REMARKS

DIMENSIONS TABLE

Unit: mm

Nominal Size	d	ANSI Class 150			D	D <sub>1</sub>	L	H	H <sub>1</sub>	H <sub>2</sub>	H <sub>3</sub>	A
		C	n	h								
400 <sup>mm</sup> 16"	394	539.5	16	29	600	470	157	451	300	382	69	400

ITEM	ROTARY DAMPER (TYPE56) ASS'Y LEVER TYPE : ANSI Class 150 400 <sup>mm</sup> (16")		
DRAWN	M.Yamamoto	DATE	SCALE
CHECKED	H.Kawano	JUL.6.2010	~
APPROVED	Y.Ozaki	DRAWING No. DP-M1001AEm	
SPECIAL ORDER No.	ASAHI YUKIZAI CORPORATION		