



1b	INSERTED METAL OF BODY	8	COPPER ALLOY (C3604)	JIS 10K
131	STEM HOLDER (C)	1	PP	
24	CAP (A)	1	PP	
23	SCREW (B)	4	STAINLESS STEEL (SUS304)	
22	LOCKING PLATE	1	PPG	
21	BOLT (B)	1	STAINLESS STEEL (SUS304)	
20	WASHER (A)	1	STAINLESS STEEL (SUS304)	
19	SPRING	1	STAINLESS STEEL (SUS304)	
18	PIN	1	PPG	
17	HANDLE LEVER	1	PPG	
16	HANDLE (A)	1	PP	
14	GLAND	1	PVDF	
13	SPACER (A)	1Set	C-PVC	
12	V-PACKING	1Set	PTFE	
10	BUSH (A)	1	PVDF	
9	BOLT · NUT (A)	3Sets	STAINLESS STEEL (SUS304)	
7	STEM	1	PVDF	
2	DISC	1	PVDF	
1	BODY	1	PVDF	
No.	DESCRIPTION	QTY.	MATERIAL	REMARKS

DIMENSIONS TABLE

UNIT : mm

NOMINAL SIZE	JIS 5K				JIS 10K																			
	d	C	n	h	C	h	N Number of Standard Bolt Holes	n Number of Through Bolt Holes	n1 Screw Holes		M	l1	l2	l3	D	D1	D2	L	H1	H2	H3	H	A	
450 ^{mm} 18"	441	555	16	25	565	27	20	16	4	8	M24	49	54	24	630	525	340	167	315	422	69	491	400	
500	20	488	605	20	25	620	27	20	16	4	8	M24	49	59	24	680	575	340	177	350	452	69	521	400
600	24	600	715	20	27	730	33	24	20	4	8	M30	64	64	30	790	686	340	197	424	517	69	586	400

NOTE. The shape and appearance of assembly differ a little with nominal size compared to this drawing.

ROTARY DAMPER (TYPE 75) ASS'Y
LEVER TYPE : □JIS5K, □JIS10K
450^{mm} (18") ~ 600^{mm} (24")

DRAWN	M.Oosako	DATE	SCALE
CHECKED	H.Kawano	NOV.15.2010	~
APPROVED	Y.Ozaki	DRAWING No. DP-M1003JE	

SPECIAL ORDER No. ASAHYUKIZAI CORPORATION