



DIMENSIONS TABLE

NOMINAL SIZE	d	DIN PN10				D	D ₁	D ₂	L	H ₁	H ₂	H ₄	H	A	
		C			n										h
		C	n	h											
450 ^{mm}	18"	441	565	20	26	630	527	340	167	315	370	126	496	323	
500	20	488	620	20	26	699	575	340	177	350	400	126	526	323	
600	24	600	725	20	30	813	692	340	197	424	465	126	591	323	

UNIT:mm

NOTE. The shape and appearance of assembly differ a little with nominal size compared to this drawing.

129	BOLT&NUT (N)	3sets	STAINLESS STEEL SUS304	
23	SCREW (B)	3	STAINLESS STEEL SUS304	
22	LOCKING PLATE	1	STAINLESS STEEL SUS304	
21	BOX NUT (B)	1	STAINLESS STEEL SUS304	
20	WASHER (A)	1	STAINLESS STEEL SUS304	
19	SPRING	1	STAINLESS STEEL SUS304	
18	PIN	1	STAINLESS STEEL SUS304	
17	HANDLE LEVER	1	STAINLESS STEEL SUS304	
16	HANDLE (A)	1	PP	
8	STEM HOLDER (A)	1	PP	
7	STEM	1	PP	
6	O-RING (C)	1	□EPDM □FPM □others ()	
2	DISC	1	PP	
1	BODY	1	PP	
No.	DESCRIPTION	No.REQ'D	MATERIAL	REMARKS

ROTARY DAMPER (TYPE 75) ASS'Y
LEVER TYPE : DIN PN10
450^{mm} (18") ~ 600^{mm} (24")

DRAWN	E.Enmei	DATE	SCALE
CHECKED	A.Kuroki	DEC.19.2001	~
APPROVED	N.Sano	DRAWING No.	
SPECIAL ORDER No.	DP-M1008DE		
ASAHI YUKIZAI CORPORATION			