



1b	INSERTED METAL OF BODY	8	COPPER ALLOY (C3604)	used for JIS 10K
131	STEM HOLDER (C)	1	PP	
24	CAP (A)	1	PP	
23	SCREW (B)	4	STAINLESS STEEL (SUS304)	
22	LOCKING PLATE	1	PPG	
21	BOLT (B)	1	STAINLESS STEEL (SUS304)	
20	WASHER (A)	1	STAINLESS STEEL (SUS304)	
19	SPRING	1	STAINLESS STEEL (SUS304)	
18	PIN	1	PPG	
17	HANDLE LEVER	1	PPG	
16	HANDLE (A)	1	PP	
9	BOLT&NUT (A)	3sets	STAINLESS STEEL (SUS304)	
6	O-RING (C)	1	□EPDM □FKM □others ( )	
7	STEM	1	PP	
2	DISC	1	PP	
1	BODY	1	PP	
No.	DESCRIPTION	QTY.	MATERIAL	REMARKS

DIMENSIONS TABLE

Nominal Size	JIS 5K				JIS 10K				Unit: mm											
	d	C	n	h	C	h	N (Number of standard bolt holes)	N (Number of through bolt holes)	n1 screw holes /side/total		M	D	D <sub>1</sub>	D <sub>2</sub>	L	H <sub>1</sub>	H <sub>2</sub>	H <sub>3</sub>	H	A
450 <sup>mm</sup> 18"	441	555	16	25	565	27	24	16	4	8	M24	630	525	340	167	315	402	69	471	400
500	488	605	20	25	620	27	24	16	4	8	M24	699	575	340	177	350	432	69	501	400
600	600	715	20	27	730	33	28	20	4	8	M30	813	686	340	197	424	497	69	566	400

NOTE. The shape and appearance of assembly differ a little with nominal size compared to this drawing.

ITEM	ROTARY DAMPER (TYPE 75) ASS'Y LEVER TYPE : □JIS 5K, □JIS 10K 450 <sup>mm</sup> (18") ~600 <sup>mm</sup> (24")		
DRAWN	M.Yamamoto	DATE	SCALE
CHECKED	H.Kawano	NOV.16.2010	
APPROVED	Y.Ozaki	DRAWING No. DP-M1008JE	
SPECIAL ORDER No.	<b>ASAHI YUKIZAI CORPORATION</b>		